

**EBERLE**

by **Schneider** Electric

In top form - the new  
RTR 9000 family





5-year warranty

48hr delivery service

## Innovative. Beautiful. Economical.

Who can claim all this? The new RTR 9000 family by Eberle can. Its high quality bimetal technology makes it every bit as precise as electronic control systems. Its attractive design brings aesthetics to any room design. Another advantage is the ease of use that distinguishes these thermostats. In terms of economy, the RTR 9000 family is leading the field. It impresses with an excellent price-performance ratio, offers a long term solution and is first class in terms of energy saving.

The RTR 9000 family by Eberle - control technology at its best.

# The stage is set for the RTR 9000 family

The RTR 9000 thermostat is equally suitable for use with electrical and hot-water heating systems. The minimalistic design has only three control elements: in addition to the rotary temperature control dial, the product family has variants with signal lamps and switches.

**RTR 9121**



## Advantages of bi-metal technology:

- Extremely durable
- Highest reliability
- Utmost precision
- Very powerful
- Exceptionally flexible
- Highly economical

## Appealing Product Features

- Stylish design
- Bi-metal technology with thermal feedback and high precision
- Surface mounting or directly onto a conduit box with vertical mounting holes
- Clear terminal arrangement and ample terminal space for quick and easy installation
- Housing in pure white, similar to RAL 9010
- Range limitation in setting dial
- Mountable on adapter frame ARA 1E

## Technical Data

Article No.	121 1101 51 100
Temperature range	5 ... 30 °C
Contact	<b>Break contact</b>
Operating voltage	230 V
Switching current	<b>Heating: 10 mA ... 10 (4) A, AC</b>
Temperature set-back (TA)	
Hysteresis	0,5 K
Switch	-
Indicator lamp	-
Protection class of housing	IP 30
Dimensions	84 x 84 x 27,5 mm

RTR 9721



RTR 9722



RTR 9724



121 1701 51 100

5 ... 30 °C

Change-over

230 V

Heating: 10 mA ... 10 (4) A, AC  
Cooling: 10 mA ... 5 (2) A, AC

0,5 K

-

-

IP 30

84 x 84 x 27,5 mm

121 1702 91 100

5 ... 30 °C

Change-over

**230 V / 24 V**

Heating: 10 mA ... 10 (4) A, AC  
Cooling: 10 mA ... 5 (2) A, AC

0,5 K

-

-

IP 30

84 x 84 x 27,5 mm

121 1707 51 100

5 ... 30 °C

Change-over

230 V

Heating: 10 mA ... 10 (4) A, AC  
Cooling: 10 mA ... 5 (2) A, AC

**TA**

0,5 K

-

-

IP 30

84 x 84 x 27,5 mm

# To be continued ...

**RTR 9725**



**RTR 9726**



**RTR 9164**



121 1719 51 100

5 ... 30 °C

Change-over

230 V

Heating: 10 mA ... 10 (4) A, AC  
Cooling: 10 mA ... 5 (2) A, AC

**TA**

0,5 K

**Mains**

**Heating**

IP 30

84 x 84 x 27,5 mm

121 1704 51 100

5 ... 30 °C

Change-over

230 V

Heating: 10 mA ... 10 (4) A, AC  
Cooling: 10 mA ... 5 (2) A, AC

**TA**

0,5 K

**Day / Night / Auto**

**Heating**

IP 30

84 x 84 x 27,5 mm

121 1121 51 100

5 ... 30 °C

**Break contact**

230 V

**8 ... 14 (4) A, AC**

**TA**


0,5 K

**Mains**

-

IP 30

84 x 84 x 27,5 mm



Scan to find out more  
[www.rtr9000.de](http://www.rtr9000.de)

# EBERLE

by **Schneider** Electric

EBERLE Controls GmbH  
Klingenhofstraße 71  
D-90411 Nürnberg  
T +49(0)911 56 93 0  
F +49(0)911 56 93 536  
E-Mail: [info.eberle@schneider-electric.com](mailto:info.eberle@schneider-electric.com)  
[www.eberlecontrols.com](http://www.eberlecontrols.com)

All specifications in this catalogue regarding our products are merely product descriptions and not legally binding. Printing errors, errors and changes - changes serving product advances also without prior notice - are reserved.

© All rights are reserved. Layout, presentation, logos, texts, graphics and pictures in this catalogue are protected by copyright.



This item is printed on environmentally friendly paper.